



Pin	Symbol
1	N.C. (GND)
2	VCC
3	VCOMH
4	IREF
5	D7
6	D6
7	D5
8	D4
9	D3
10	D2
11	D1
12	D0
13	E/RD#
14	R/W#
15	D/C#
16	RES#
17	CS#
18	N.C.
19	BS2
20	BS1
21	VDD
22	N.C.
23	N.C.
24	VBREF
25	N.C.
26	FB
27	VDDb
28	GDR
29	VSS
30	N.C. (GND)

Notes:

1. Color: Yellow
2. Driver IC: SSD1305
3. Die Size: 8200um x 1200um
4. TCP Number: SSD1305T7
5. Interface:
8-bit 68XX/80XX Parallel, 4-wire SPI, I2C
6. General Tolerance: ±0.30
7. The total thickness (2.10 Max) is without polarizer protective film, remove tape.
The actual assembled total thickness with above materials should be 2.35 Max.

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI12864WO-Y	
ENGR CHK	mm	MODEL	
APPROVAL		DWG NO	
MULTI-INNO TECHNOLOGY CO.,LTD.		PAGE	
		1/1	