



|                |
|----------------|
| 环保标准           |
| ■ ROHS标准       |
| □ 《 有害物质管理标准 》 |

PIN DESCRIPTION

| NO. | SYMBOL | NO. | SYMBOL |
|-----|--------|-----|--------|
| 1   | NC     | 17  | CS#    |
| 2   | VCC    | 18  | NC     |
| 3   | VCOMH  | 19  | BS2    |
| 4   | IREF   | 20  | BS1    |
| 5   | D7     | 21  | VDD    |
| 6   | D6     | 22  | NC     |
| 7   | D5     | 23  | NC     |
| 8   | D4     | 24  | NC     |
| 9   | D3     | 25  | VBREF  |
| 10  | D2     | 26  | NC     |
| 11  | D1     | 27  | FB     |
| 12  | D0     | 28  | VDD    |
| 13  | E/RD#  | 29  | GDR    |
| 14  | R/W#   | 30  | VSS    |
| 15  | D/C#   | 31  | NC     |
| 16  | RES#   |     |        |

- NOTES:
1. OPERATING TEMP: -20° C TO 70° C
  2. STORAGE TEMP: -30° C TO 80° C
  3. VIEWING DIRECTION: ALL
  4. OLED DRIVE IC: SSD1305T7R1
  5. DISPLAY COLOR: White
  6. UNSPECIFIED TOLERANCES: ± 0.2mm.
  7. ( ) MEANS: DIMENSION FOR REFERENCE
  8. THE PROTECTIVE FILMS ON THE SIDE OF OLED MUST BE REMOVED BEFORE ASSEMBLY BY CUSTOMER (客户在装机时, 自己必须撕掉保护膜)

|                                |       |             |      |
|--------------------------------|-------|-------------|------|
| CUSTOMER APVL                  |       | DATE        |      |
| DRAWN                          | SCALE | TITLE       |      |
| DFTG CHK                       | UNIT  | MI13216BO-W |      |
| ENGR CHK                       | mm    | MODEL       |      |
| APPROVAL                       |       | MODEL       |      |
| MULTI-INNO TECHNOLOGY CO.,LTD. |       | DWG NO      | PAGE |
|                                |       |             | 1/1  |