



40 PIN FUNCTIONS											
1	U/D	11	VSS	21	G5	31	R3				
2	NC	12	ADJ	22	G4	32	VSS				
3	HSYNC	13	B5	23	G3	33	R2				
4	VLED	14	B4	24	VSS	34	R1				
5	VLED	15	B3	25	G2	35	R0				
6	VLED	16	VSS	26	G1	36	VSS				
7	VCC	17	B2	27	G0	37	VSS				
8	VSYNC	18	B1	28	VSS	38	DCLK				
9	DE	19	B0	29	R5	39	VSS				
10	VSS	20	VSS	30	R4	40	L/R				

Note:

- Brightness : 400 cd/m² (Typ)
- 40 PIN Connector: JAE FA5B040HP1 or Equivalent.
- 10 PIN Connector: Molex: 54548-1071 or Equivalent.
- Tolerance is ±0.3 unless otherwise noted.
- For RoHS.

CUSTOMER APVL	CUSTOMER	DATE	TITLE	
DRAWN	SCALE	TITLE	MI0570ET-5	
DFTG CHK	UNIT	MODEL		
ENGR CHK	mm			
APPROVAL		DWG NO	PAGE	
MULTI-INNO TECHNOLOGY CO.,LTD.			1/1	