



PIN	SYMBOL
1	VCOM
2	NC
3	VGL
4	C4P
5	C4N
6	VGH
7	FRP
8	VCAC
9	VDD_25
10	C3P
11	C3N
12	VDD3
13	C2P
14	C2N
15	VDDA
16	C1P
17	C1N
18	GND
19	VDD
20	DRV
21	VLED
22	NC
23	FB
24	NC
25	AGND
26	VDDIO
27	CSB
28	SDA
29	SCL
30	HSYNC
31	VSYNC
32	DCLK
33	D7
34	D6
35	D5
36	D4
37	D3
38	D2
39	D1
40	D0

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VDD=3.3V
3. VIEWING DIRECTION: 6 O'CLOCK.
4. IC DRIVER: OTA5182A
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 2-CHIP WHITE LED.
8. GENERAL TOLERANCE: ±0.2.
9. RoHS COMPLIANT.

CUSTOMER APVL		DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0236AT-3	
ENGR CHK	mm	MODEL	
APPROVAL			
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE
		01	1/1