


PIN	Symbol
1	VLED-
2	VLED+
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	HSYN
33	VSIN
34	DE
35	IOVCC_HVDSL
36	GND
37	NC
38	NC
39	NC
40	NC

CTP FPC:

1	VSS
2	VDD
3	SCL(SSEL)
4	NC(SCK)
5	SDA(MOSI)
6	NC(MISO)
7	RST
8	WAKE
9	INT
10	VSS



- NOTES FOR TFT:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE
 2. OPERATION VOLTAGE: VDD=3.3V
 3. VIEWING DIRECTION: 12 O'CLOCK.
 4. IC DRIVER: ILI6480BQ
 5. OPERATING TEMP: -20°C ~ 70°C.
 6. STORAGE TEMP: -30°C ~ 80°C.
 7. LED BACKLIGHT: 10-LED WHITE, If=40mA, Vf=16V.
 8. GENERAL TOLERANCE: ±0.3.
 9. RoHS COMPLIANT.

- NOTES FOR CTP:
1. 4.3 INCH PROJECTIVE CAPACITIVE TOUCH PANEL.
 2. OPERATION VOLTAGE: VDD=3.3V
 3. COVER GLASS + SENSOR GLASS + FPCA.
 4. RESOLUTION: 480 X 272 DOTS
 5. IC DRIVER: FT5306 (SMT).
 6. MULTI FINGER: UP TO 5.
 7. HARDNESS OF COVER SURFACE: 7H.

MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY: CAROL	2015.03.18	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI0430H1T-9
APPROVED BY:			DESCRIPTION:
VERSION NO: 01	DATE		TFT MODULE

01	FIRST ISSUE	2015.03.18
VER.	REVISED DESCRIPTION	DATE