



- Note:
- Luminance :  $400 \text{ cd/m}^2$  (Typ.)
  - Uniformity : 70%
  - LCD FPC Match Connector: Molex 054104-4031 or equivalent
  - Tolerance is  $\pm 0.3$  unless otherwise noted.
  - The bending radius of FPC should be larger than 0.6mm
  - for RoHS
  - Bending Area
  - \* is important dimension.

PIN FUNCTIONS

1 VLED-	11 R6	21 B0	31 DISP
2 VLED+	12 R7	22 B1	32 Hsync
3 GND	13 G0	23 B2	33 Vsync
4 VDD	14 G1	24 B3	34 NC
5 R0	15 G2	25 B4	35 NC
6 R1	16 G3	26 B5	36 GND
7 R2	17 G4	27 B6	37 NC
8 R3	18 G5	28 B7	38 NC
9 R4	19 G6	29 GND	39 NC
10 R5	20 G7	30 PCLK	40 NC

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0430J1T-1	
ENGR CHK	mm	MODEL	
APPROVAL		DWG NO	
MULTI-INNO TECHNOLOGY CO.,LTD.		PAGE	1/1