


- Note:
1. Luminance : 320 cd/m² (Typ.)
 2. Uniformity : 70%
 3. LCD FPC Match Connector: Molex 054104-4031 or equivalent
 4. Tolerance is ±0.3 unless otherwise noted.
 5. The bending radius of FPC should be larger than 0.6mm
 6. for RoHS
 7. Bending Area
 8. * is important dimension.
 9. Surface treatment: Anti-Glare, Anti-Smudge.



PIN FUNCTIONS

1 VLED-	11 R6	21 B0	31 DISP
2 VLED+	12 R7	22 B1	32 Hsync
3 GND	13 G0	23 B2	33 Vsync
4 VDD	14 G1	24 B3	34 NC
5 R0	15 G2	25 B4	35 NC
6 R1	16 G3	26 B5	36 GND
7 R2	17 G4	27 B6	37 X+
8 R3	18 G5	28 B7	38 X-
9 R4	19 G6	29 GND	39 Y+
10 R5	20 G7	30 PCLK	40 Y-

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0430J1T	
ENGR CHK	mm	MODEL	
APPROVAL			
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE
			1/1