



PIN	Symbol
1	VLED-
2	VLED+
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	R0
22	R1
23	R2
24	R3
25	R4
26	R5
27	R6
28	R7
29	GND
30	DCLK
31	DISP
32	HSYN
33	VSYN
34	DE
35	NC
36	GND
37	NC
38	NC
39	NC
40	NC

CTP FPC:

1	VSS
2	VDD
3	SCL(SSEL)
4	NC(SCK)
5	SDA(MOSI)
6	NC(MISO)
7	RST
8	WAKE
9	INT
10	VSS

- NOTES FOR TFT:
1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
 2. OPERATING VOLTAGE: VDD=3.3V.
 3. VIEWING DIRECTION: 6 O'CLOCK.
 4. IC DRIVER: HX8257A.
 5. OPERATING TEMP: -20°C ~ 70°C.
 6. STORAGE TEMP: -30°C ~ 80°C.
 7. LED BACKLIGHT: 10-CHIP WHITE LED, If=40mA, Vf=16V.
 8. SURFACE LUMINANCE: 380cd/m²(TYP.)
 9. TREATMENT OF TOP SURFACE: ANTI-GLARE.
 10. GENERAL TOLERANCE: ±0.3.
 11. RoHS COMPLIANT.

- NOTES FOR CTP:
1. 4.3 INCH PROJECTIVE CAPACITIVE TOUCH PANEL.
 2. OPERATING VOLTAGE: VDD=3.3V.
 3. COVER GLASS + SENSOR GLASS + FPÇA.
 4. RESOLUTION: 480 X 272 DOTS.
 5. IC DRIVER: FT5306 (SMT).
 6. MULTI FINGER: UP TO 5.
 7. HARDNESS OF COVER SURFACE: 7H.

Mit MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL	2015.04.24	SCALE : 1/1	MODULE P/N:
CHECKED BY:			UNIT:	MI0430K1T-1CP
APPROVED BY:			mm	DESCRIPTION:
VERSION NO:	01			TFT MODULE

VER.	REVISED DESCRIPTION	DATE
01	First issue	2015.04.24