


16-BIT MODE(CN2)	
Pin No.	Symbol
1	GND
2	VCC
3	BL_E
4	RS
5	/WR
6	/RD
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	DB8
16	DB9
17	DB10
18	DB11
19	DB12
20	DB13
21	DB14
22	DB15
23	NC
24	NC
25	/CS
26	/RST
27	NC
28	X1
29	Y1
30	X2
31	Y2
32	DISP

NOTES:

1. DISPLAY TYPE: TN TFT
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSMISSIVE/POSITIVE
4. VCC=3.3V(TYP)
5. OPERATING TEMP: -20° C -- +70° C
6. STORAGE TEMP: -30° C -- +80° C
7. LCD CONTROLLER: SSD1963
8. INTERFACE: 16-BIT 8080 MPU
9. BACKLIGHT: WHITE LED
10. UNMARKED TOLERANCE: ±0.30mm
11. REQUIREMENTS ON ENVIRONMENTAL PROTECTION: RoHS



CUSTOMER APVL		DATE	2013/01/14	
DRAWN BY JACK		SCALE	1/1	
DFTG CHK		UNIT	mm	
ENGR CHK				
APPROVAL				
MULTI-INNO TECHNOLOGY CO.,LTD.			DWG NO	PAGE
			V01	1