



LED K LED A  
 Voltage :25.6 V (Typ.)  
 Current :20 mA (Typ.)  
Backlight Circuit

- NOTE:
1. For RoHS
  2. Match connector : Hirose FH39-45S-0.3SHW or equivalent.
  3. The bending radius of FPC should be large than 0.5 mm.
  4. Tolerance is ±0.3 unless otherwise noted.
  5. \* is important dimension.
  6. is Stiffener.
  7. Uniformity: 70% (Min).
  8. Center Brightness: 320cd/m<sup>2</sup> (Min.), 400cd/m<sup>2</sup> (Typ.).

1	VDD
2	VDD
3	GND
4	GND
5	VDDI
6	VDDI
7	NC
8	NC
9	NC
10	RESX
11	R5
12	R4
13	R3
14	R2
15	R1
16	R0
17	G5
18	G4
19	G3
20	G2
21	G1
22	G0
23	B5
24	B4
25	B3
26	B2
27	B1
28	B0
29	VS
30	HS
31	GND
32	PCLK
33	GND
34	DE
35	SDI
36	NC
37	CSX
38	SCL
39	NC
40	NC
41	NC
42	GND
43	GND
44	LEDK
45	LEDA



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2014.05.25	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI0430YT-1
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		TFT MODULE

01	FIRST ISSUE	2014.05.25
VER.	REVISED DESCRIPTION	DATE