



1	LED_A
2	LED_K
3	GND
4	GND
5	VCC(3.3V)
6	VDDIO
7	VSYNC
8	HSYNC
9	DE
10	PCLK
11	RESET
12	CS
13	SCL
14	SDI
15	SDO
16	DB0(B0)
17	DB1
18	DB2
19	DB3
20	DB4
21	DB5
22	DB6
23	DB7(B7)
24	GND
25	DB8(G0)
26	DB9
27	DB10
28	DB11
29	DB12
30	DB13
31	DB14
32	DB15(G7)
33	GND
34	DB16(R0)
35	DB17
36	DB18
37	DB19
38	DB20
39	DB21
40	DB22
41	DB23(R7)
42	GND

NOTES:

1. DISPLAY TYPE: IPS TFT,NORMALLY BLACK.
2. OPERATING VOLTAGE: VCC=3.3V.
3. VIEWING DIRECTION: FULL VIEWING ANGLE.
4. IC DRIVER: HX8369A.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 8CHIP- WHITE LED, If=40mA,Vf=12.8V.
8. CONNECTOR TYPE: 05002HR-H42J05(G).
8. GENERAL TOLERANCE: ±0.2.
9. RoHS COMPLIANT.

MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY:	CAROL 2014.10.16	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI0430ZT-1
APPROVED BY:			DESCRIPTION:
VER.	01		TFT MODULE

01	FIRST ISSUE	2014.10.16	APPROVED BY:
VER.	REVISED DESCRIPTION	DATE	VERSION NO: 01