



LCD FPC FUNCTIONS			
1 VLED-	11 R6	21 B0	31 DISP
2 VLED+	12 R7	22 B1	32 Hsync
3 GND	13 G0	23 B2	33 Vsync
4 VDD	14 G1	24 B3	34 DE
5 R0	15 G2	25 B4	35 NC
6 R1	16 G3	26 B5	36 GND
7 R2	17 G4	27 B6	37 NC
8 R3	18 G5	28 B7	38 NC
9 R4	19 G6	29 DGND	39 NC
10 R5	20 G7	30 DCLK	40 NC

Note:

- Center Luminance : 450 cd/m² (Typ.)
360 cd/m² (Min.)
- Uniformity : 70% (Min)
- Surface treatment: Anti-glare.
- * is important dimension.
- Tolerance is ±0.3 unless otherwise noted.
- The bending radius of FPC should be larger than 0.6mm
- LCD FPC match connector:HIROSE FH19SC-40S-0.5SH or equivalent
- For RoHS & REACH



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2014.06.27	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT:	MI0500YT-1
APPROVED BY:		mm	DESCRIPTION:
VERSION NO:	01		TFT_MODULE

01	FIRST ISSUE	2014.06.27
VER.	REVISED DESCRIPTION	DATE