



CN1 Pin Assign

1	GND
2	DOTCLK
3	Hsync
4	Vsync
5	GND
6	R0
7	R1
8	R2
9	R3
10	R4
11	R5
12	GND
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	GND
20	B0
21	B1
22	B2
23	B3
24	B4
25	B5
26	GND
27	ENABLE
28	VCC
29	VCC
30	R/L
31	U/D
32	NC
33	GND

Notes:

1. Unmarked tolerance: ±0.50mm;
2. Display Type: a-Si TFT;
3. Operating Temperature: -30°C~+85°C;
4. Storage Temperature: -30°C~+85°C;
5. Gray Scale Inversion: 12 o'clock; Viewing Direction: 6 o'clock;
6. CN2 LED Power source Connector: SHLP-06V-S-B(JST) or Compatible, Mating Connector: SM06B-SHLS-TF(JST) or Compatible;
7. CN1 Connector type: 089H33-000100-G2-R (STARCONN)
8. Requirement on Environment Protection: RoHS Compliant.

CN2 Pin Assign

PIN NO	Symbol	Cable color
1	AN1	Red
2	AN2	Red
3	AN3	Red
4	CA1	White
5	CA2	Blue
6	CA3	Black

CUSTOMER APVL		CUSTOMER		DATE
DRAWN	SCALE	TITLE		
DFTG_CHK	UNIT	MI0570PT		
ENGR_CHK	mm	MODEL		
APPROVAL		DWG NO		
MULTI-INNO TECHNOLOGY CO.,LTD.				PAGE 1/1