






MODULE NO.: MI0700AJT-1

Ver 1.0



Pin	Symbol
1	GND
2	GND
3	MC
4	VCC
5	VCC
6	VEE
7	VCC
8	MC
9	DE
10	GND
11	GND
12	GND
13	B5
14	B4
15	B0
16	GND
17	B2
18	B1
19	B0
20	GND
21	G5
22	G4
23	G3
24	GND
25	G2
26	G1
27	G0
28	GND
29	R5
30	R4
31	R3
32	GND
33	R2
34	R1
35	R0
36	GND
37	GND
38	DCLK
39	GND
40	GND



NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VDD=3.3V
3. VIEWING DIRECTION: 12 O'CLOCK.
4. DRIVER IC: HX8262+HX8678.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 24-CHIP WHITE LED, If=160mA, Vf=9.6V.
8. GENERAL TOLERANCE: ±0.3mm.
9. RoHS COMPLIANT.

01	First issue	2014.11.27
VER.	REVISED DESCRIPTION	DATE

MULTI-INNO TECHNOLOGY CO.,LTD.			
DRAWN BY:	CAROL 2014.11.27	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI0700AJT-1
APPROVED BY:			DESCRIPTION:
VERSION NO:	01		TFT MODULE