


P/In	Symbol
1	END
2	END
3	NC
4	VCC
5	VCC
6	VCC
7	VCC
8	NC
9	RE
10	END
11	END
12	END
13	RS
14	R4
15	RS
16	END
17	RE
18	R1
19	R0
20	END
21	G5
22	G4
23	G3
24	END
25	G2
26	G1
27	G0
28	END
29	F5
30	R4
31	R3
32	END
33	R2
34	R1
35	R0
36	END
37	END
38	EXL4
39	END
40	END

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VDD=3.3V
3. VIEWING DIRECTION: 12 O'CLOCK.
4. DRIVER IC: HX8262+HX8678.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. LED BACKLIGHT: 24-CHIP WHITE LED, If=160mA, Vf=9.6V.
8. GENERAL TOLERANCE: ±0.3mm.
9. RoHS COMPLIANT.



TP:

P/N	Assignment
1	Y+
2	X+
3	Y-
4	X-



MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2014.11.27	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT:	MI0700AJT-2
APPROVED BY:		mm	DESCRIPTION:
VERSION NO:	01		TFT MODULE

01	First issue	2014.11.27
VER.	REVISED DESCRIPTION	DATE