


LED circuit



Detail "A"
SCALE 5:1

Touch Panel Pin Assignment

PIN #	Description
1	Top
2	Right
3	Bottom
4	Left

- NOTE:
1. Tolerance is ± 0.3 unless otherwise noted.
 2. Touch-panel front surface is antiglare treatment.
 3. Touch Panel flex tail do not bend to less than 3.175mm radius.
 4. For RoHS.
 5. * is important dimension.
 6. CN1 connector: Hirose DF14A-20P-1.25H or equivalent, matching side connector: Hirose DF14-20S-1.25C or equivalent.
 7. CN6 connector: Hirose DF14A-5P-1.25H or equivalent, matching side connector: Hirose DF14-5S-1.25C or equivalent.

CN6 PIN FUNCTION

1 VDD	3 GND	5 ADJ
2 VDD	4 GND	

CN1 PIN FUNCTION

1 Vcc	6 RxIN0+	11 RxIN2-	16 GND
2 Vcc	7 GND	12 RxIN2+	17 VDD
3 GND	8 RxIN1-	13 GND	18 VDD
4 GND	9 RxIN1+	14 CKIN-	19 GND
5 RxIN0-	10 GND	15 CKIN+	20 ADJ

CUSTOMER APVL	CUSTOMER	DATE	TITLE
DRAWN	SCALE	MI0700J1T	
DFTG CHK	UNIT		
ENGR CHK	mm		
APPROVAL			MODEL
MULTI-INNO TECHNOLOGY CO.,LTD.			DWG NO
			PAGE 1/1