


**Note:**

1. Brightness : 720 cd/m<sup>2</sup> (Typ) 640 cd/m<sup>2</sup> (Min)
2. 40 PIN Connector: JAE FA5B040HP1 or Equivalent.
3. Tolerance is ±0.3 unless otherwise noted.
4. For RoHS.
5. \* is important dimension.



40 PIN FUNCTIONS									
1	U/D	11	Y1	21	G5	31	R3		
2	NC	12	ADJ	22	G4	32	VSS		
3	HSYNC	13	B5	23	G3	33	R2		
4	VLED	14	B4	24	VSS	34	R1		
5	VLED	15	B3	25	G2	35	R0		
6	VLED	16	VSS	26	G1	36	X1		
7	VCC	17	B2	27	G0	37	Y2		
8	VSYNC	18	B1	28	VSS	38	DCLK		
9	DE	19	B0	29	R5	39	VSS		
10	X2	20	VSS	30	R4	40	L/R		

CUSTOMER APVL	CUSTOMER	DATE		
DRAWN	SCALE	TITLE	MI0570ET-10	
DFTG CHK	UNIT	MODEL		
ENGR CHK	mm			
APPROVAL				
MULTI-INNO TECHNOLOGY CO.,LTD.			DWG NO	PAGE
				1/1