



TRULY: DF37B-24DP-0.4V(S1)
CUSTOMER: DF37B-24DS-0.4V(S1)

焊锡高度0.3MAX
注意避空

单层区域

1.60" TFT
240(H)XRGBX240(V) Dots

viewing direction area for both human eyes and sun glass application

TO 7:00 O'CLOCK

FROM 5:00 O'CLOCK

29.40 (机壳推荐开窗)

34.00 TFT

35.10±0.15 FRAME

28.80 A.A

0.30MAX

(1.20)

(0.90)

(0.20)

1.50±0.15 不包括FPC

环保标准	
■	ROHS标准
□	《 有害物质管理标准》

LED A LED K

IF=20MA, VF=9 V(TYP.)

SCALE:50/1

弯折示意图

封口位注意避空

PIN	NAME	PIN	NAME
1	GND	13	IM1
2	/RESET	14	/RD
3	GND	15	/WR
4	DB8	16	RS
5	DB7	17	/CS
6	DB6	18	IDVCC
7	DB5	19	FMARK
8	DB4	20	VCI
9	DB3	21	GND
10	DB2	22	LEDA
11	DB1	23	LEDK
12	DB0	24	GND

备注要求:

- LCD显示模式: TRANSFLECTIVE, NORMALLY WHITE(TF-E2)
- LCD 驱动IC:ST7789S
- 操作温度: -20° C~+70° C
- 存储温度: -30° C~+80° C
- VIEW DIRECTION:TBD
- BACK LIGHT:3WHITE LED
- 组装前请撕掉正面和反面的保护膜; 焊接位不可接触导体

展开出货

CUSTOMER APVL		DATE	
DRAWN	SCALE X.X ±0.3	TITLE MI0160AT-1	
DFTG CHK	X.XX ±0.2		
ENGR CHK	ANGULAR:±1/4°	MODEL	
APPROVAL	UNIT mm		
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE 1/1