

PINS ASSIGNMENTS



NO.	SYMBOL	NO.	SYMBOL
1	GND	21	G5
2	GND	22	G4
3	NC	23	G3
4	VCC	24	GND
5	VCC	25	G2
6	VCC	26	G1
7	VCC	27	G0
8	NC	28	GND
9	DE	29	R5
10	GND	30	R4
11	GND	31	R3
12	GND	32	GND
13	B5	33	R2
14	B4	34	R1
15	B3	35	R0
16	GND	36	GND
17	B2	37	GND
18	B1	38	DCLK
19	B0	39	GND
20	GND	40	GND

TP:


P/N	Assignment
1	Y+
2	X+
3	Y-
4	X-

NOTES:

1. DISPLAY TYPE: TFT, TRANSMISSIVE, NORMALLY WHITE.
2. OPERATING VOLTAGE: VDD=3.3V
3. VIEWING DIRECTION: 12 O'CLOCK.
4. DRIVER IC: HX8262+HX8678.
5. OPERATING TEMP: -20°C ~ 70°C.
6. STORAGE TEMP: -30°C ~ 80°C.
7. SURFACE LUMINANCE: 800cd/m²(TYP).
8. LED BACKLIGHT: 15-CHIP WHITE LED, If=260mA.
9. UPPER POLARIZER TYPE: GLARE.
10. GENERAL TOLERANCE: ±0.3mm.
11. RoHS COMPLIANT.




DETAIL A SCALE 4/1



Backlight Circuit (3*5=15LED, 260mA)

CONNECTOR MATED FPC/FCC STYLE (SCALE 2:1)



MIT MULTI-INNO TECHNOLOGY CO.,LTD.

DRAWN BY:	CAROL 2015.04.17	SCALE : 1/1	MODULE P/N:
CHECKED BY:		UNIT: mm	MI0700AJT-5RP
APPROVED BY:		DESCRIPTION:	TFT MODULE
VERSION NO:	01		

VER.	REVISED DESCRIPTION	DATE
01	First issue	2015.04.17